

Y-Type Strainer

No.	Parts Name	Qty.	Materials
1	Body	1	ASTM A 216 Gr.WCB
			ASTM A 351 Gr.CF8
			ASTM A 351 Gr. CF8M
			GM(85/5/5/5)
			IS 210 Gr.220
2	Stud Nut	4/8/12	ASTM A 193 Gr.B7
			ASTM A 193 Gr.2H
			S.S. 304
3	Screen	1	S.S. 304
			S.S. 304
			GM
			GM
4	Cover	1	ASTM A 216 Gr.WCB
			ASTM A 351 Gr.CF8
			ASTM A 351 Gr. CF8M
			IS 210 Gr.220
			Alloy 20

Technical Data	
Face to Face :	As per DIN ND – 40 Type
End Connections :	Flanged as per DIN 2533 / 2543 / 2535 / 2545 Screwed BSP Socket / Weld to ANSI B 16.34



Available Size	
Size in mm	Size in inch
15mm	1/2"
20mm	3/4"
25mm	1"
32mm	1-1/4"
40mm	1-1/2"
50mm	2"
65mm	2-1/2"
80mm	3"
100mm	4"
125mm	5"
150mm	6"

Service Rating	
40 Kg / cm ²	400° C

Hydraulic Test Pressure	
Body	80 Kg / cm ²